

D100

m-tec D100 Continuous Mixer

With a conveying performance of 100 l/min, mixer D100 is certainly powerful. It is designed to process dry mortar products with a granularity of up to 6 mm and is found on numerous building sites throughout the world. The D100 optimizes the processing of bricklaying and insulating mortar, plasters, screeds or fine concrete.

Fitted with a powerful 5.5 kW motor it mixes even heavy products with ease. The direct mounting on the silo creates a compact unit that speeds up work on the building site whatever the weather.

As is typical of all m-tec systems, the D100 has easy and quick to use connector systems that enable important elements, such as the mixing chamber or mixer motor, to be replaced in just a few seconds.

The m-tec S100 control panel is the control unit for mixer D100. It can cope with every situation and a number of different versions are available in line with the performance of the continuous mixer. Starting from a hand-operated, economical basic model and ranging to a fully automatic version with remote control, timer and special control, the m-tec S100 control panels meet every challenge a modern building site can produce.



- Delivery volume: standard approx. 100
 I/min (depending on the transport and mixing shaft)
- Drive motor: 5.5kW, 400 V, 50 Hz
- Weight 150kg
- Dimensions 230 x 38 x 35 cm

Lawn Road Industrial Estate, Carlton in Lindrick, Worksop, Notts, S81 9LB. England.

TEL: +44 (0) 1909 730861 FAX: +44 (0) 1909 733584 www.markham-sheffield.co.uk